

## Paint Filling Machine : Full automatic filling line



[Click here](#)

### Usage

It mainly applies for dosing & mouth-sealing automatic production line for chemical raw materials, especially for industrial coating, oil, and also for food, pharmacy industry( Customer should provide the materials sample and part characteristics parameter.)

### Performance Features

The whole line is an intelligent product integrating of mechanism, electric and air. It consists of stainless steel dynamic roller conveying line, pail-on, filling, cover-on, cover-pressing, electrical control, vacuum system etc. It can unit with computer in central control room( Optional) to realize functions such as modern management, malfunction alarm, indicating etc.

Automatization programming control is divided into two parts: Automatic control and manual control:

On automatic control page: Press” Automatic”, the whole machine will starts automatically according to the set order.

On manual control page: It is mainly used when equipment commissioning and maintenance is required. Manual control buttons: Each button has its own action. The light of the button shinning means it is working.

Weighing sector : little error , static error  $\leq 0.13\%$  , dynamic error  $\leq 0.25\%$ .

Equipment Name	Model Technical Parameter	FL10-30-T
Computer dosing filling machine	Weighing range ( kg )	10-30
	Filling speed ( times/h )	160-240
	Allow tolerance	±0.2%
	Electrical source	AC380V 50Hz±2Hz
	Air source	Flux: 0.1m <sup>3</sup> /min Pressure:0.4 ~ 0.6MPa
	Power: KW	4
	Work temperature	0 ~ 40
	Shape size (mm)	Subject to the provided shape drawing
	Weight ( kg )	1050